

Topy Speedy L

Distinguishing mark			
1.1	Model designator		Topy Speedy L
1.2	Drive unit		Electrics
1.3	Operator type		Pedestrian
1.4	Rated capacity	kg	1800
1.5	Load Centre distance	mm	600
1.6	Load distance	mm	945
1.7	Wheelbase	mm	1270
Weights			
2.1	Service weight (include battery)	kg	285
2.2	Axle loading, laden driving side//loading side	kg	770/1315
2.3	Axle loading without load, unladen driving side/loading side	kg	230/55
Wheels/tyres			
3.1	Tyre type driving wheels/loading wheels		PU/PU
3.2	Tyre size, driving wheels (diameter x width)	mm	230x75
3.3	Tyre size, loading wheels (diameter x width)	mm	74x88 / 80x60
3.4	Tyre size, caster wheels (diameter x width)	mm	85x48
3.5	Wheels, number driving, caster/loading (x=drive wheels)	mm	1x+2/2 / 1x+2/4
3.6	Track width, front driving side	mm	435
3.7	Track width, rear, loading side	mm	390/495/535
Dimensions			
4.1	Lift height	mm	108
4.2	Height drawbar in driving position min./max	mm	715/1200
4.3	Lowered height	mm	85
4.4	Overall leght	mm	1625
4.5	Length to face of forks	mm	475
4.6	Overall width	mm	645
4.7	Fork dimension	mm	50x150x1150
4.8	Outside width of the forks	mm	540/645/685
4.9	Ground clarence, center of wheelbase	mm	35
4.10	Aisle width for pallets 1000 x 1200 crossways	mm	1720
4.11	Aisle width for pallets 800 x 1200 lenghtways	mm	1920
4.12	Turning radius	mm	1465
Performarce data			
5.1	Travel speed, laden/unladen	km/h	5.5/6
5.2	Lifting speed, laden/unladen	m/s	0.051/0.060
5.3	Lowering speed laden/unladen	m/s	0.32/0.39
5.4	Max. gradeability, with/ without load	%	01-giu
5.5	Service brake		Electromagnetic
Electric-engine			
6.1	Drive motor rating S2 60 min	kW	1.1
6.2	Lift motor rating at S3 15%	Kw	0.84
6.3	The maximum allowed size battery	mm	269x182x300
6.4	Battery voltage/nominal capacity K20	V/Ah	2x 12/85
6.5	Battery weight	Kg	25x2
Addition data			
7.1	Type of drive control		AC
7.2	Steering type		Mechanical
7.3	Sound pressure level at the driver's eat		74

If there are improvements of technical parameters or configurations, no further notice will be given.

The diagram shown may contain non-standard configurations.